

# PowerWalker VI 800 SW

## Line-Interactive UPS

800VA Line-Interactive UPS with pure Sine Wave

3x IEC, RJ-11 and RJ-45 Surge Protection


USB Connection for monitoring

LCD display for status view

Built-in boost and buck AVR function



Item-No. 10120062



### Product Features

With its digitalized PWM-based controller PowerWalker VI 800 SW provides a pure sine wave output especially best suitable to protect modern PC like mini servers, gaming PC, point of sale (POS) systems and other electronic devices with APFC power supplies. Not only limited to APFC power supplies and equipped with a voltage stabilizer, this UPS will continue providing clean and stable power to connected equipment and is perfect for any home or small and medium office application.

- Pure Sine Wave
- Super smart charger to shorten charging time
- Built-in boost and buck AVR
- Auto restart while AC is recovering
- Off-mode charging
- Cold start function
- USB communication port
- RJ-11, RJ-45 surge protection
- Monitoring software included
- LCD display for status view



Backsite view



LCD Display



USB port,  
RJ-11, RJ-45 surge  
Protection

## Technical Details

### Product Features

Capacity	800VA / 480W
<b>Input</b>	
Voltage	220/230/240VAC
Voltage Range	162-290VAC

### Output

Voltage	220/230/240VAC
Voltage Regulation (Battery Mode)	± 10 %
Frequency	50 or 60Hz
Freq. Regulation (Battery Mode)	± 1 Hz (Battery Mode)
Waveform	Pure Sine Wave

### Transfer Time

Typical	2-6ms
---------	-------

### Battery

Type	12V / 9Ah
Quantity	1x
Recharge Time	4h to 90%

### LCD Display

Indicators	AC mode, Battery mode, Load level, Battery capacity, Input voltage, Output voltage, Overload alarm, Fault alarm and Low battery alarm
------------	---

### Audio Indicators

Battery Mode	Beep every 10 sec
Low Battery	Beep every second
Fault	Continuous Beep
Battery is faulty	Beep every 2 sec
UPS overload	Beep 2 times per second

### Full Protection

Discharge	Yes
Overcharge	Yes
Overload	Yes
Short circuit	Yes

### Connections

Communication	USB
Outlets	3x IEC
Surge Protection	RJ-11, RJ-45 (in/out)

### Software & System Requirements

Software	ViewPower
Operating System	For details visit: <a href="http://www.powerwalker.com/viewpower.html">www.powerwalker.com/viewpower.html</a>
Other	1x USB port

### Product Details

Dimensions	328 x 100 x 145 mm
Colour	Black
Weight	6.0 kg
Model Code	VI 800 SW

### Environment

Temperature	0°C – 40°C
Humidity	0 – 90 % RH (non-condensing)

### Package Content

Package Content	PowerWalker VI 800 SW, Input Power Cord, IEC-Cable C13/C14, USB Cable, Control Software CD, Manual
-----------------	--

### Logistic Data

Giftbox Language	EN/DE/FR/ES/IT/PT/SV/FI/NO/TR RU/UA/BY/PL/CZ/HU/BG/KK/SR
Manual Language	EN/DE/FR/ES/IT/PT/RU/PL
Dimension/Giftbox	385 x 140 x 228 mm
Weight/Giftbox	tba
Dimension/Carton	tba
Weight/Carton	tba
Pieces/Carton	4
Pieces/Palette	128
Item Number	10120062
EAN	4260074975529
Warranty	24 Month (except battery)