

M Series Small Size Non-Touch Monitor

True Flat Display



Features and Benefits

- ◆ USB or VGA Interface Available
- ◆ Durable Die-Casting Aluminum Base for Option
- ◆ 7", 8" and 10" Pole Base for Option
- ◆ Easy for Installation - Only USB Cable Needed
- ◆ Spill Proof and Anti-Dust
- ◆ Best Choice for Space Limited Retail / Hospitality Settings
- ◆ True Flat Designed to Suit Harsh Environment

M363

M354

M365



OTEKsys

M Series Small Size Non-Touch Monitor

OTEK_{sys}



USB Interface Available



VGA Interface Available



True Flat Design



Wall Mount Available



Die-Casting Base for Option



7", 8" and 10" Pole Base for Option

Specification

MODEL NAME	M363ND	M363NC	M354ND	M354NC	M365ND	M365NC
Display Size	7"		8"		10.4"	
Optimal Resolution	800 * 480		800 * 600		800 * 600	
Panel Brightness	350 cd/m² (typ)		350 cd/m² (typ)		350 cd/m² (typ)	
Contrast Ratio	500:1 (typ)		500:1 (typ)		500:1 (typ)	
Response Time	25 ms (typ)		25 ms (typ)		20 ms (typ)	
Viewing Angle(L / R / U / D)	70 / 70 / 50 / 70		70 / 70 / 50 / 70		70 / 70 / 50 / 60	
Tilt Angle	35°C(V) / 70°C(H) w/pole		N/A		N/A	
Input Video signal	DIN	USB B Type	DIN	USB B Type	DIN	USB B Type
Power consumption	6W	2.5W	6W	2.5W	8W	2.5W
Input Frequency	Horizontal: 31.5-60.2 kHz ; Vertical : 56.3Hz~75Hz					
Power supply	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%
Temperature	Operating : 0°C~40°C(32 F ~ 104 F) ; Storage : -10°C~50°C (14 F ~ 122 F)					
Humidity	Operating : 20%~80% ; Storage : 10%~90%					
Weight	0.5Kg (1.27lbs)		0.7Kg (1.78lbs)		0.85Kg (2.16lbs)	
Physical Dimension WxHxD	184.5*118*34.5 (mm) 72.7*46.5*13.6 (inch)		202*163*34.5 (mm) 79.6*64.2*13.6 (inch)		244*197.4*36.4 (mm) 96.1*77.8*14.3 (inch)	
Optional	White, Wall Mount Kit					

* This specification is subject to change without prior notice.

OTEK SYSTEM CO., LTD.

Address: 6F., No.30, Singjhong Rd., Neihu District, Taipei, Taiwan Tel: +886-2-7720-1688 Fax: +886-2-7721-2188

http://www.oteksys.com E-mail:sales@oteksys.com

