



AMPLIFIERS

AS039

Features

Easy installation
Innovative product design
Two outputs
Gain adjustment

Technical specifications

Amplification: 20 dB
Gain adjustment: 12 dB
Connectors: F-connectors
Forward path: 16 dB / 47 MHz; 20 dB / 862 MHz
Power consump.: 3 W / 230 V AC/ 50 Hz

Dimensions and weight:

Unit (WxDxH): 60 x 40 x 130 mm
Unit (Net weight): 0.34 Kg
Giftbox (WxDxH): 97 x 50 x 175 mm
Gross Weight: 0.32 Kg

EAN number: 5706998023216
Item number: 4315
Carton QTY: 40

Contents:

Amplifier

AS039R65

Features

With return path
Easy installation
Innovative product design
Two outputs
Gain adjustment

Technical specifications

Amplification: 20 dB
Gain adjustment: 12 dB
Connectors: F-connectors
Forward path: 16 dB / 47 MHz; 20 dB / 862 MHz
Power consump.: 3 W / 230 V AC/ 50 Hz
Return path: 5 – 65 MHz: -5 dB

Dimensions and weight:

Unit (WxDxH): 60 x 40 x 130 mm
Unit (Net weight): 0.34 Kg
Giftbox (WxDxH): 97 x 50 x 175 mm
Gross Weight: 0.32 Kg

EAN number: 5706998023223
Item number: 4316
Carton QTY: 40

Contents:

Amplifier