



6° Monoblock LNBs

Features

- 6° Monoblock Single LNB
- For 1 Receiver and 2 satellite positions
- Gold connectors
- Latest PLL Technology
- High Performance
- Low noise
- Weather boots included

Features

- 6° Monoblock Twin LNB
- For 2 Receivers and 2 satellite positions
- Gold connectors
- Latest PLL Technology
- High Performance
- Low noise
- Weather boots included

Features

- 6° Monoblock Quad LNB
- For 4 Receivers and 2 satellite positions
- Gold connectors
- Latest PLL Technology
- High Performance
- Low noise
- Weather boots included

Technical specifications

Noise Figure
0.1 dB (typ.)

Input Frequency range
10.7-12.75 GHz

Output Frequency Range
950-2150 MHz

LO
9.75/10.6GHz

Power consumption
130MA(Max.)

High Gain
57-66 dB

Neck Size
40 mm

Operation Temperature
-35°C to 60°C

Dimensions and weight

Package (HxWxD): 102x121x67 mm
Package (Weight): 0.25 kg

EAN number: 5711783914365
Item number: MAXI5621PQ
Carton QTY: 50

Technical specifications

Noise Figure
0.1 dB (typ.)

Input Frequency range
10.7-12.75 GHz

Output Frequency Range
950-2150 MHz

LO
9.75/10.6GHz

Power consumption
250MA(Max.)

High Gain
54-67 dB

Neck Size
40 mm

Operation Temperature
-35°C to 60°C

Dimensions and weight

Package (HxWxD): 105x122x105 mm
Package (Weight): 0.25 kg

EAN number: 5711783914372
Item number: MAXI5622PQ
Carton QTY: 30

Technical specifications

Noise Figure
0.1 dB (typ.)

Input Frequency range
10.7-12.75 GHz

Output Frequency Range
950-2150 MHz

LO
9.75/10.6GHz

Power consumption
250MA(Max.)

High Gain
54-67 dB

Neck Size
40 mm

Operation Temperature
-35°C to 60°C

Dimensions and weight

Package (HxWxD): 105x122x105 mm
Package (Weight): 0.25 kg

EAN number: 5711783914389
Item number: MAXI5624PQ
Carton QTY: 30