



# User Manual

USB 3.1 Type-C to USB3.0X4+Type-C Charging



ES623007WH

# Contents

---

- 1.0 Introduction
- 2.0 Features
- 3.0 Specifications
- 4.0 Package contents
- 5.0 Operation
- 6.0 Connection diagram

## DEAR CUSTOMER

Thank you for purchasing this product. For optimum performance and safety, please read these instructions carefully before connecting, operating or using this product. Please keep this manual for future reference.

## 1.0 Introduction

---

This is a USB-C to USB 3.0 four ports with USB-C charging port hub. The four USB3.0 port allow you to connect four USB devices to a host computer or another hub and the USB-C female port can charge for the host computer. It can work on Macbook or Google new Chromebook Pixel and other USB-C supported devices charging.

## 2.0 Features

---

- Support USB-C input, USB3.0 Output
- Among the 4 USB 3.0 ports, one port supports BC 1.2, the power of this port can be up to 7.5W (5V/1.5A)
- Support USB 3.0 super speed (5Gbps) transmission, downward compatible with USB2.0
- USB-C female charging port for Macbook or Google new Chromebook Pixel and other USB-C supported devices charging
- Multiple USB-C interfaces support plug and play, hot swap
- Easy to use and carry

## 3.0 Specifications

Input/Output Connector	
Input	USB-C Male x1
Output	USB 3.0 Female x4; USB-C Female x1 for charging
Physical	
Weight	40.5g
Size (L-W-H)	93x40x11 (mm)
Warranty	
Limited Warranty	1 year
Frequency	
Operating Frequency	5Gbps transmission data
Environmental	
Operating Temperature	0°C to +45°C
Operating Humidity	10% to 90% RH (no condensation)
Storage Temperature	-10°C to +70°C
Storage Humidity	10% to 90 % RH (no condensation)
Power Supply	
USB-C PD charging Port	60W (20V/3A)
USB-C Female Charging Port	Max 1.5A for BC1.2 port (only one port is connected) Max 900mA per port for the other three ports (only one port is connected) Max 1.5A when four ports are connected
Regulatory Approvals	
Certifications	FCC,CE
Accessory Adapter	
User Manual	English Version

## 4.0 Package contents

---

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- Main unit x1
- User Manual x1

## 5.0 Operation

---

- 1) Connect the USB-C male port of this product to computer.
- 2) Connect the four USB3.0 ports to USB devices.
- 3) Connect the USB-C charging port, it can charge for the host computer and support this adapter to work simultaneously

Note:

- 1) When connecting the USB-C male port of the adapter to Chromebook, the mouse to be connected to the USB 3.0 port will not work immediately, it will have seconds' delay. This problem also occurs in other similar type-c adapter (including Apple original 3 in 1 Adapter) when connected to Chromebook.
- 2) When plugging in or out the PD Adapter, the connected USB devices will get disconnected flashily and then reconnect in a few seconds, so to prevent possible data loss or corruption, avoid disconnecting the PD Adapter from AC power while transferring data

## 6.0 Connection diagram



**eSTUFF**

Please note that all names, models and trademarks are the sole property of their respective owners. **eSTUFF®** is a registered trademark of EET Group A/S. Device composition and illustration shown on the packaging is for informative purposes only and may differ from the actual product.

Imported into the EU by EET Group A/S  
Tempovej 41, 2750 Ballerup, Denmark

Designed in Denmark  
Made in China

[www.estuff.eu](http://www.estuff.eu)

