



- NOTES:**
- 1.Operation Temperature:-40°C~+85°C.
 - 2.Electrial Characteristics:
 - 2.1>Rated Current : 125V AC,1.5A@25°C.
 - 2.2>Contact Resistance : 20mΩ Max.
 - 2.3>Insulation Resistance:500MΩ Min,100V DC/min.
 - 2.4>Voltage Proof: 1000V AC/1 minute no breakdown
 - 3.Mechanical Characteristics:
 - 3.1>Insertion Force & Withdrawal Force : 30N Max.
 - 3.2>Durability:750 cycles Min.
 - 4.Environmental compliance:
 - 4.1>the products are compliant with the RoHS, and REACH etc.

ITEM NO:	LAN125306			DRAWER DATE	20240122
TITLE				CHECKED DATE	ACE 20240122
CUSTOMER				APPROVED DATE	
MATERIAL		SCALE			
REV.	A	UNIT	MM		
DRAWING NO:	40122081				
ACAD FILE	E:\				

1	Modular Plug	Contacts 8PCS	2 Prongs <input type="checkbox"/>	G/F <input type="checkbox"/>	1u" <input type="checkbox"/>	3u" <input checked="" type="checkbox"/>	6u" <input type="checkbox"/>	Brass <input checked="" type="checkbox"/>
			3 Prongs <input checked="" type="checkbox"/>	15u" <input type="checkbox"/>	30u" <input type="checkbox"/>	50u" <input type="checkbox"/>	other <input type="checkbox"/>	Phosphor copper <input type="checkbox"/>
		Housing 1PC	transparent PC				94V-2 <input checked="" type="checkbox"/> 94V-0 <input type="checkbox"/>	
NO.	NAME	QTY	DESCRIPTION				MATERIAL	