

Specification for C28 Blower 2-in-1 (10000mAh)



Specifications description	3-section 3300mAh battery
Model	C28 suck and blow 2-in-1
Material	ABS+PP
Size	160*100*65mm (excluded tube)
Electric motor	395 brushed motor
Fan leaf	Aluminum alloy
P C B	FR4
Batteries	18650*3
Capacity	11.1V 2000mAh
Turn on/off	Touch switch
Cable/wire	Pure Copper
Product packing-box	210*140*70mm
Product weight	695g
Carton Size	440*368*372mm 25pcs/ctn
Gross weight	18.3kg
Input voltage	5V
Input current	2A
Output voltage	11.1V
Output current	6~9A (max)
Rated power	68W
Charging time	3.5~4.5H
Noise decibel	≤90DB
Wind speed flow rate	51000RPM
Pressure (full charge)	First gear: 2.5~3.0kpa Second gear: 3.5~4.0kpa Third gear: 5.5~6.0kpa
Blowing force range (full charge)	First gear: 28g±2g 25000 rpm Second gear: 38g±2g 37000 rpm Third gear: 48g±2g 51000 rpm
Usage duration (full charge)	First gear: 42±2 mins Second gear: 29±2 mins Third gear: 19±2 mins
Oversupply protection	Yes
Overcurrent protection	Yes
Overdischarge protection	Yes
Short circuit protection	Yes
Reversed-Battery Protection	Yes
Operation Instructions	①Press and hold for 3 seconds to turn on the device, default to first gear. ②Press the button once to switch to second gear after turning on the device. ③Press the button again to switch to third gear. ④Press the button once more to pause (automatically shut down if no operation within one minute).
Indicator light display	①Red light flashes during charging ②Blue light stays on when fully charged ③Blue light when working
Product certification	CE FCC ROHS
Battery certification	UN38.3; MSDS; Air transport report; Sea transport report; KC
Patent	Domestic (China)
Packaging list	4x blowing nozzles/1x brush tube/1x vacuum cup/1x flat nozzle brush tube/1x instruction manual 1x cable 1x dust blower